


Maxstar Wedge V-Belts for RMA / MPTA



Section	bo (in)	h (in)
3V/9N (3VX)	0.38	0.33
5V/15N (5VX)	0.63	0.55
8V/25N	1.00	0.88

Belt indication

5V 1000

Cross Section

Belt Code(inch×10)

Table 1-6

3V(3VX)-Section		5V(5VX)-Section		8V-Section	
Belt Code	Effective length Le (in)	Belt Code	Effective length Le (in)	Belt Code	Effective length Le (in)
250	25	500	50	1000	100
265	26.5	530	53	1060	106
280	28	560	56	1120	112
300	30	600	60	1180	118
315	31.5	630	63	1250	125
335	33.5	670	67	1320	132
355	35.5	710	71	1400	140
375	37.5	750	75	1500	150
400	40	800	80	1600	160
425	42.5	850	85	1700	170
450	45	900	90	1800	180
475	47.5	950	95	1900	190
500	50	1000	100	2000	200
530	53	1060	106	2120	212
560	56	1120	112	2240	224
600	60	1180	118	2360	236
630	63	1250	125	2630	263
670	67	1320	132	2500	250
710	71	1400	140	2650	265
750	75	1500	150	2800	280
800	80	1600	160	3000	300
850	85	1700	170	3150	315
900	90	1800	180	3350	335
950	95	1900	190	3550	355
1000	100	2000	200	3750	375
1060	106	2120	212	4000	400
1120	112	2240	224	4250	425
1180	118	2360	236	4500	450
1250	125	2500	250	4750	475
1320	132	2650	265	5000	500
1400	140	2800	280	5600	560
		3000	300	6000	600
		3150	315		
		3350	335		
		3550	355		

: Available size for Raw Edge Cogged V-Belts 3VX & 5VX

